HPC Specifications

Call for quotations as per the following requirements: Amount should of Inclusive of Taxes, Delivery at university, inclusive of Installation and training.

Master Node with internal 25TB usable storage - 1 No

Sku Description	Quantity
PowerEdge R740 Server OR Equavalent model from any company	1
Chassis with up to 8 x 3.5" SAS/SATA Hard Drives for 2CPU Configuration	1
Intel Xeon Silver 4114 2.2G, 10C/20T, 9.6GT/s , 14M Cache, Turbo, HT (85W) DDR4-2400	2
Standard 1U Heatsink	1
2666MT/s RDIMMs	1
Performance Optimized	1
32GB RDIMM 2666MT/s Dual Rank	2
RAID 5	1
PERC H330 RAID Controller, Adapter, Low Profile	1
8TB 7.2K RPM NLSAS 12Gbps 3.5in Hot-plug Hard Drive	5
iDRAC9,Enterprise	1
OME Server Configuration Management	1
Broadcom 5720 QP 1Gb Network Daughter Card	1
Riser Config 3, 2 x8, 3 x16 slots	1
Intel Omni-Path Host Fabric Adapter 100 Series 1 Port PCIe x16	1
HPC BIOS Settings	1
6 Standard Fans for R740/740XD	1
Dual, Hot-plug, Redundant Power Supply (1+1), 750W	1
Jumper Cord,10A,4M,C13/C14 (India BIS)	2
Red Hat Linux Registration Document, No Subscription	1
Enterprise Linux OS, Non Factory Installed, Requires Subscription Selection	1
Red Hat Enterprise Linux,2SKT,1 Physical OR 2Guest,3Yr PREMIUM SUB,No Media	1
3Yr ProSupport: Next Business Day Onsite Service	1
3Yr ProSupport:(7x24) Technical Support & Assistance	1
Basic Deployment Dell Server R Series 1U/2U	1
PowerEdge 2U Standard Bezel	1
ReadyRails Sliding Rails Without Cable Management Arm	1
DVD+/-RW,SATA,Int	1
iDRAC Group Manager, Enabled	1
iDRAC,Factory Generated Password	1
iDRAC,Factory Generated Password	1

Compute Node with GPU - 1 no

Sku Description	Quantity
PowerEdge R740 Server OR Equavalent model from any company	1
Chassis with up to 8 x 2.5" SAS/SATA Hard Drives for 2CPU Configuration	1
Intel Xeon Gold 5120 2.2G, 14C/28T, 10.4GT/s , 19.25M Cache, Turbo, HT (105W) DDR4-2400	2
HS Install Kit,GPU Config, EPS12V Cable	1
2666MT/s RDIMMs	1
Performance Optimized	1
32GB RDIMM 2666MT/s Dual Rank	8
RAID 1	1
PERC H330 RAID Controller, Adapter, Low Profile	1

IDRAC9,Enterprise 1 OME Server Configuration Management 1 Broadcom 5720 QP 1Gb Network Daughter Card 1 Riser Config 4, 3x8, 4 x16 slots 1 Intel Omni-Path Host Fabric Adapter 100 Series 1 Port PCle x16 1 NVIDIA Tesla V100 16G Passive GPU 1 HPC BIOS Settings 1 1 6 Performance Fans forR740/740XD 1 Dual, Hot-plug, Redundant Power Supply (1+1), 1600W, 250 Volt Power Cord Required for Use 1 Jumper Cord, 10A, 4M, C13/C14 (India BIS) 2 Enterprise Linux OS, Non Factory Installed, Requires Subscription Selection 1 Red Hat Enterprise Linux for HPC, 1-2 Socket, 3yr Subscription and License 1 3Yr ProSupport: (7x24) Technical Support & Assistance 1 Basic Deployment Dell Server R Series 1U/2U 1 PowerEdge 2U Standard Bezel 1 ReadyRails Sliding Rails Without Cable Management Arm 1 DVD+/-RW,SATA,Int 1 Technical Support 1		
OME Server Configuration Management Broadcom 5720 QP 1Gb Network Daughter Card Riser Config 4, 3x8, 4 x16 slots Intel Omni-Path Host Fabric Adapter 100 Series 1 Port PCle x16 NVIDIA Tesla V100 16G Passive GPU 1 HPC BIOS Settings 1 6 Performance Fans forR740/740XD 1 Dual, Hot-plug, Redundant Power Supply (1+1), 1600W, 250 Volt Power Cord Required for Use 1 Jumper Cord,10A,4M,C13/C14 (India BIS) Enterprise Linux OS, Non Factory Installed, Requires Subscription Selection Red Hat Enterprise Linux for HPC, 1-2 Socket, 3yr Subscription and License 1 3Yr ProSupport: Next Business Day Onsite Service 1 3Yr ProSupport: (7x24) Technical Support & Assistance 1 Basic Deployment Dell Server R Series 1U/2U PowerEdge 2U Standard Bezel ReadyRails Sliding Rails Without Cable Management Arm 1 DVD+/-RW,SATA,Int Technical Support 1	1TB 7.2K RPM SATA 6Gbps 512n 2.5in Hot-plug Hard Drive	2
Broadcom 5720 QP 1Gb Network Daughter Card Riser Config 4, 3x8, 4 x16 slots Intel Omni-Path Host Fabric Adapter 100 Series 1 Port PCle x16 NVIDIA Tesla V100 16G Passive GPU HPC BIOS Settings 6 Performance Fans forR740/740XD Dual, Hot-plug, Redundant Power Supply (1+1), 1600W, 250 Volt Power Cord Required for Use 1 Jumper Cord,10A,4M,C13/C14 (India BIS) Enterprise Linux OS, Non Factory Installed, Requires Subscription Selection Red Hat Enterprise Linux for HPC, 1-2 Socket, 3yr Subscription and License 3Yr ProSupport: Next Business Day Onsite Service 1 3Yr ProSupport: (7x24) Technical Support & Assistance 1 Basic Deployment Dell Server R Series 1U/2U PowerEdge 2U Standard Bezel ReadyRails Sliding Rails Without Cable Management Arm 1 DVD+/-RW,SATA,Int Technical Support 1 Technical Support	iDRAC9,Enterprise	1
Riser Config 4, 3x8, 4 x16 slots Intel Omni-Path Host Fabric Adapter 100 Series 1 Port PCle x16 NVIDIA Tesla V100 16G Passive GPU HPC BIOS Settings 1 6 Performance Fans forR740/740XD 1 Dual, Hot-plug, Redundant Power Supply (1+1), 1600W, 250 Volt Power Cord Required for Use 1 Jumper Cord,10A,4M,C13/C14 (India BIS) 2 Enterprise Linux OS, Non Factory Installed, Requires Subscription Selection 1 Red Hat Enterprise Linux for HPC, 1-2 Socket, 3yr Subscription and License 3Yr ProSupport: Next Business Day Onsite Service 3Yr ProSupport: (7x24) Technical Support & Assistance Basic Deployment Dell Server R Series 1U/2U 1 PowerEdge 2U Standard Bezel ReadyRails Sliding Rails Without Cable Management Arm 1 DVD+/-RW,SATA,Int 1 Technical Support 1	OME Server Configuration Management	1
Intel Omni-Path Host Fabric Adapter 100 Series 1 Port PCIe x16 NVIDIA Tesla V100 16G Passive GPU HPC BIOS Settings 6 Performance Fans forR740/740XD Dual, Hot-plug, Redundant Power Supply (1+1), 1600W, 250 Volt Power Cord Required for Use 1 Jumper Cord,10A,4M,C13/C14 (India BIS) Enterprise Linux OS, Non Factory Installed, Requires Subscription Selection Red Hat Enterprise Linux for HPC, 1-2 Socket, 3yr Subscription and License 3Yr ProSupport: Next Business Day Onsite Service 13Yr ProSupport:(7x24) Technical Support & Assistance Basic Deployment Dell Server R Series 1U/2U 1 PowerEdge 2U Standard Bezel ReadyRails Sliding Rails Without Cable Management Arm 1 DVD+/-RW,SATA,Int Technical Support 1	Broadcom 5720 QP 1Gb Network Daughter Card	1
NVIDIA Tesla V100 16G Passive GPU HPC BIOS Settings 6 Performance Fans forR740/740XD 1 Dual, Hot-plug, Redundant Power Supply (1+1), 1600W, 250 Volt Power Cord Required for Use 1 Jumper Cord, 10A, 4M, C13/C14 (India BIS) Enterprise Linux OS, Non Factory Installed, Requires Subscription Selection Red Hat Enterprise Linux for HPC, 1-2 Socket, 3yr Subscription and License 1 3Yr ProSupport: Next Business Day Onsite Service 1 3Yr ProSupport: (7x24) Technical Support & Assistance Basic Deployment Dell Server R Series 1U/2U PowerEdge 2U Standard Bezel ReadyRails Sliding Rails Without Cable Management Arm 1 DVD+/-RW,SATA,Int 1 Technical Support	Riser Config 4, 3x8, 4 x16 slots	1
HPC BIOS Settings 6 Performance Fans forR740/740XD 1 Dual, Hot-plug, Redundant Power Supply (1+1), 1600W, 250 Volt Power Cord Required for Use 1 Jumper Cord,10A,4M,C13/C14 (India BIS) 2 Enterprise Linux OS, Non Factory Installed, Requires Subscription Selection 1 Red Hat Enterprise Linux for HPC, 1-2 Socket, 3yr Subscription and License 1 3Yr ProSupport: Next Business Day Onsite Service 1 3Yr ProSupport: (7x24) Technical Support & Assistance 1 Basic Deployment Dell Server R Series 1U/2U 1 PowerEdge 2U Standard Bezel 1 ReadyRails Sliding Rails Without Cable Management Arm 1 DVD+/-RW,SATA,Int 1 Technical Support 1	Intel Omni-Path Host Fabric Adapter 100 Series 1 Port PCIe x16	1
6 Performance Fans forR740/740XD Dual, Hot-plug, Redundant Power Supply (1+1), 1600W, 250 Volt Power Cord Required for Use 1 Jumper Cord,10A,4M,C13/C14 (India BIS) Enterprise Linux OS, Non Factory Installed, Requires Subscription Selection Red Hat Enterprise Linux for HPC, 1-2 Socket, 3yr Subscription and License 3Yr ProSupport: Next Business Day Onsite Service 1 3Yr ProSupport:(7x24) Technical Support & Assistance Basic Deployment Dell Server R Series 1U/2U PowerEdge 2U Standard Bezel ReadyRails Sliding Rails Without Cable Management Arm DVD+/-RW,SATA,Int 1 Technical Support	NVIDIA Tesla V100 16G Passive GPU	1
Dual, Hot-plug, Redundant Power Supply (1+1), 1600W, 250 Volt Power Cord Required for Use Jumper Cord,10A,4M,C13/C14 (India BIS) Enterprise Linux OS, Non Factory Installed, Requires Subscription Selection Red Hat Enterprise Linux for HPC, 1-2 Socket, 3yr Subscription and License 3Yr ProSupport: Next Business Day Onsite Service 3Yr ProSupport:(7x24) Technical Support & Assistance Basic Deployment Dell Server R Series 1U/2U 1 PowerEdge 2U Standard Bezel ReadyRails Sliding Rails Without Cable Management Arm 1 DVD+/-RW,SATA,Int Technical Support 1	HPC BIOS Settings	1
Jumper Cord,10A,4M,C13/C14 (India BIS) Enterprise Linux OS, Non Factory Installed, Requires Subscription Selection Red Hat Enterprise Linux for HPC, 1-2 Socket, 3yr Subscription and License 3Yr ProSupport: Next Business Day Onsite Service 3Yr ProSupport:(7x24) Technical Support & Assistance Basic Deployment Dell Server R Series 1U/2U PowerEdge 2U Standard Bezel ReadyRails Sliding Rails Without Cable Management Arm 1 DVD+/-RW,SATA,Int Technical Support 1	6 Performance Fans forR740/740XD	1
Enterprise Linux OS, Non Factory Installed, Requires Subscription Selection Red Hat Enterprise Linux for HPC, 1-2 Socket, 3yr Subscription and License 3Yr ProSupport: Next Business Day Onsite Service 3Yr ProSupport:(7x24) Technical Support & Assistance Basic Deployment Dell Server R Series 1U/2U PowerEdge 2U Standard Bezel ReadyRails Sliding Rails Without Cable Management Arm 1 DVD+/-RW,SATA,Int Technical Support 1	Dual, Hot-plug, Redundant Power Supply (1+1), 1600W, 250 Volt Power Cord Required for Use	1
Red Hat Enterprise Linux for HPC, 1-2 Socket, 3yr Subscription and License 3Yr ProSupport: Next Business Day Onsite Service 3Yr ProSupport:(7x24) Technical Support & Assistance Basic Deployment Dell Server R Series 1U/2U 1 PowerEdge 2U Standard Bezel ReadyRails Sliding Rails Without Cable Management Arm 1 DVD+/-RW,SATA,Int Technical Support 1	Jumper Cord,10A,4M,C13/C14 (India BIS)	2
3Yr ProSupport: Next Business Day Onsite Service 1 3Yr ProSupport: (7x24) Technical Support & Assistance 1 Basic Deployment Dell Server R Series 1U/2U 1 PowerEdge 2U Standard Bezel 1 ReadyRails Sliding Rails Without Cable Management Arm 1 DVD+/-RW,SATA,Int 1 Technical Support 1	Enterprise Linux OS, Non Factory Installed, Requires Subscription Selection	1
3Yr ProSupport:(7x24) Technical Support & Assistance Basic Deployment Dell Server R Series 1U/2U PowerEdge 2U Standard Bezel ReadyRails Sliding Rails Without Cable Management Arm DVD+/-RW,SATA,Int Technical Support 1	Red Hat Enterprise Linux for HPC, 1-2 Socket, 3yr Subscription and License	1
Basic Deployment Dell Server R Series 1U/2U PowerEdge 2U Standard Bezel ReadyRails Sliding Rails Without Cable Management Arm DVD+/-RW,SATA,Int Technical Support 1	3Yr ProSupport: Next Business Day Onsite Service	1
PowerEdge 2U Standard Bezel 1 ReadyRails Sliding Rails Without Cable Management Arm 1 DVD+/-RW,SATA,Int 1 Technical Support 1	3Yr ProSupport:(7x24) Technical Support & Assistance	1
ReadyRails Sliding Rails Without Cable Management Arm 1 DVD+/-RW,SATA,Int 1 Technical Support 1	Basic Deployment Dell Server R Series 1U/2U	1
DVD+/-RW,SATA,Int 1 Technical Support 1	PowerEdge 2U Standard Bezel	1
Technical Support 1	ReadyRails Sliding Rails Without Cable Management Arm	1
	DVD+/-RW,SATA,Int	1
PowerEdge R740/R740XD Motherboard 1	Technical Support	1
	PowerEdge R740/R740XD Motherboard	1

Compute Node - 2 No

Sku Description	Quantity
PowerEdge R440 Server OR Equavalent model from any company	1
3.5" Chassis with up to 4 Hot Plug Hard Drives	1
Internal PERC	1
Intel Xeon Gold 5120 2.2G, 14C/28T, 10.4GT/s , 19.25M Cache, Turbo, HT (105W) DDR4-2400	2
Standard Heat Sink	1
Standard Heat Sink for 2nd CPU	1
2666MT/s RDIMMs	1
Performance Optimized	1
32GB RDIMM 2666MT/s Dual Rank	8
RAID 1	1
PERC H330 RAID Controller, Adapter, Low Profile	1
1TB 7.2K RPM SATA 6Gbps 512n 3.5in Hot-plug Hard Drive	2
iDRAC9,Enterprise	1
OME Server Configuration Management	1
Riser Config 3, 2 x 16 LP	1
Broadcom 5720 DP 1Gb Network Interface Card, Low Profile	1
Intel Omni-Path Host Fabric Adapter 100 Series 1 Port PCIe x16, Low Profile	1
Dual-Port 1GbE On-Board LOM	1
Performance BIOS Settings	1
Dual, Hot Plug, Redundant Power Supply (1+1), 550W	1
Jumper Cord,10A,4M,C13/C14 (India BIS)	2
Enterprise Linux OS, Non Factory Installed, Requires Subscription Selection	1
Red Hat Enterprise Linux for HPC, 1-2 Socket, 3yr Subscription and License	1
3Yr ProSupport: Next Business Day Onsite Service	1
3Yr ProSupport:(7x24) Technical Support & Assistance	1

Basic Deployment Dell Server R Series 1U/2U	1
Standard Bezel	1
ReadyRails Sliding Rails Without Cable Management Arm	1
DVD +/-RW, SATA, Internal	1
iDRAC Group Manager, Enabled	1
iDRAC,Factory Generated Password	1
Technical Support	1
Motherboard	1

Primary Interconnect Switch - 1 No

Sku Description	Quantity
Dell Networking H1024-OPF, 24 port unmanaged Edge Switch, 1U, (2) 110/220VAC PSU, PSU to I/O air	1
flow	1
Dell Networking OmniPath Cable, QSFP28 to QSFP28, Passive Copper Direct Attach Cable, 3 Meter,	5
UL1581	J
Deskside Power Cord, GType, 230V,2M (Nepal, Sri Lanka, India)	2
2M Rack Power Cord C13/C14 12A	2
3Yr ProSupport: Next Business Day Onsite Service	1
3Yr ProSupport: 7x24 Tech Support & Assistance	1
3Yr Technical Support	1

Management Switch - 1 No

Sku Description	Quantity
Dell Networking N1524, 24x 1GbE + 4x 10GbE SFP+ fixed ports, Stacking, IO to PSU airflow, AC	1
Jumper Cord,10A,2M,C13/C14 (India BIS)	1
Dell Networking, N1500, User Documentation	1
Lifetime Limited Hardware Warranty (POW)	1
Basic Deployment Dell Networking N Series 1XXX/2XXX Switch	1
Lifetime Limited Dell Standard Technical Support	1

Rack, KVM, Sliding Display etc

Overall HPC Cluster setup and configuration

Sku Description	Quantity
DellEMC Rack 42U, 600W, 1000mmD #ARW9UXQ-QCKA5855-00	1
Dell DMPU108e 8-port remote KVM switch with one remote, one local user, single power supply	1
Dell LED KMM, 18.5", 1U, International English Keyboard - DKMMLED185 - 001	1
DMPUIQ-VMCHS for Dell SIM for VGA interface. For Dell DMPU Console PE KVMs, VM, CAC & USB2.0	6
DELL DRMK-77 for Dell only oneU KVM mounting braket for Dell 185FPM and DKMMLED185 LED KMM Console	1
PDU Vertical IEC C13 12x10 Amp, C19 4x16 Amp with 32 Amp MCB and Indicator with 3mtr Cable and Industrial Plug	2
Total	
Software & Installation	
HPC Software Stack	Qty
Installation and Configuration of following -	
ROCKS or xCAT Open Source Cluster Management Software	
Job Scheduler Software (Open Grid Engine Scheduler)	Set
C/C++, Fortran Compilers and Parallel Libraries	